



LAUNDRY

WASHER EXTRACTOR SB-485



AVAILABLE OPTIONS

- Automatic drum positioning
- Electrical heating
- Direct steam heating
- Pneumatic door lock
- EMI filter for CE
- 2nd water drain
- Extra inlet connection with or without valve

STANDARD FEATURES



- Advanced microprocessor
- Compartment supply dispenser
- All wetted parts are stainless
- 300G extraction force
- Built in vacuum breaker
- Variable frequency drive
- Stainless steel cabinet
- Freestanding construction and suspension systems allow for stability and performance. Spring suspension is standard for 60 & 80 pound models, while the larger models have the air cushion.
- Large door opening and reliable door lock make loading and unloading fast with the flexibility of the door. The door opening system is engineered to make operation safe easy and reliable.
- 5 compartment supply dispensers for both liquid and detergent. They are automatically flushed during each cycle
- 6 external liquid supply connections
- Electronically controlled motor is operated by a variable frequency drive protects motor from overload while saving energy, & still performing at higher extract speeds that are time efficient.
- Solid bearing housing structure
- Single or double motor drive
- Straight down drain for drain pit
- Inverter drive: Programmable variable speed
- Standard voltages: 380-415/50/3, 208-240/50/60/3 or 440-460/60/3
- PLC assisted control

WASHER EXTRACTOR SB-485

Technical Data

Washer capacity	219.99 Kg (485 lbs.)
Drum dimensions (Ø x P)	1400 mm x 1430 mm 2200L 2.2m³ basket volume
Door opening (L x W)	1160 mm x 450 mm
Motor	18.5kW 25 HP *2 motors
Wash speed	32 RPM 0.8 G
Extraction speed	620 RPM (Medium) 650 RPM (High)
Drain system (Optional)	76.2mm outlet 1866L/min capacity 1(2) drain outlet(s)
Chemical supply system	5 dry chemical compartments liquid supply connections: 1/2"
Steam consumption (Pressure)	640 Kg/hr 8.6 bar
Inlets	3/4" (Water) 1/2" (Steam) 2 water inlets 1 steam
Machine dimensions (LxWxH)	2155 mm x 2585 mm x 2625 mm
Air compression	8.6 Kg/cm² 3/8" connection
Net weight (Shipping)	5097 Kg (5193 Kg)

Detail & Dimensions



As continued product improvement is a policy of Powerline, specifications are subject to change without notice.



POWERLINE EQUIPMENT COMPANY

Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlinelaundry.com