



LAUNDRY

DEEP CHEST IRONER PFC-64x120-1



STANDARD FEATURES

- 1 roll
- Steam heating
- Variable speed with soft-start
- Easy to use electronic temperature and speed control with digital readout
- Pneumatically controlled compression rolls with automatic adjustment of pressure
- Roll can be raised and locked pneumatically in an extra wide position for easy maintenance
- Electrical and mechanical protection devices
- Three phase electrical service
- High polished heated chest
- Liftoff interlocked panels for easy maintenance
- Independent suction fans for moisture evaporation
- Signal lamps indicating operational status
- Low working pressure signal lamp
- Standard voltages: 380-415/50/3, 208-240/50/60/3 or 440-460/60/3

AVAILABLE OPTIONS



- 4 rolls configuration
- Canopy for energy saving and heat elimination
- Nomex padding for longevity
- Hot oil heated
- Special widths (3000, 3500, or 4000 mm)
- Audible signal alarms for low pressure

DEEP CHEST IRONER PFC-64x120-1

Technical Data

Roller diameter	1600 mm
Working width	3000 mm
Speed range	6-30 m/min
Drive motor (Circulate)	15 kW 20 HP (11 kW 15 HP)
Feed belt (Blower motor)	0.75 kW 1 HP (1.1 kW 1.5 HP)
Air flow	90cmm
Exhaust duct	279.4 mm
Gas inlet (Steam)	25.4mm (63.5mm) *38.1mm steam outlet
Steam consumption (Pressure)	391.2 Kg/hr (6.2-10.35 bar)
Air inlet & vent	12.7 mm
Machine dimensions (LxWxH)	3362 mm (Steam) 3462 mm (Hot Oil) x 4880 mm x 2320 mm
Net weight	7441 Kg (Steam) 7691 Kg (Hot Oil)
Shipping weight	8843 Kg (Steam) 9093 Kg (Hot Oil)

Detail & Dimensions



As continued product improvement is a policy of Powerline, specifications are subject to change without notice.



POWERLINE EQUIPMENT COMPANY

Pulaski Street, Norwalk, CT 06851 USA. Tel: 203-847 2357 Fax: 203-847 6480

www.powerlinelaundry.com