



LAUNDRY

TUMBLE DRYER PES-14



STANDARD FEATURES

- Drum in stainless steel AISI 304
- External panels painted with epoxy powder
- Huge fluff filter, easily cleaned
- IM 7 microprocessor with 30 customizable programs
- Self-diagnostic with 11 available languages
- Drying parameters can be temporarily modified while the program is running
- Cooling cycle at the end of the program, additional cooling can be programmed at the beginning as well
- The heating cycle is composed of freely programmable steps
- The no wrinkle cycle ensures the finishing is easier, complimented by the universal drying of the reversing drum equipped with dry control. Great for delicate fabrics
- High Safety: The cycle stops when the door is opened at any time

AVAILABLE OPTIONS

- DSC: The drum speed can be programmed and modified standard for 1ph 230V models
- FSC: Suction fan speed can be controlled (Not for gas dryers)
- Power control: The electric heated dryer can work at full or partial power
- The dryer is available in fully stainless steel. Frontal panels also available for order
- Available in gas, steam, or electric
- Coin operated: Coin box, prepaid key or central cash

TUMBLE DRYER

PES-14

Technical Data

Washer capacity	14Kg
Drum dimensions (ØxP)	756 mm x 585 mm (560mm load Ø)
Drum speed	38 RPM
Electric heating element	6 x 3 Kw
Steam heating power (Pressure)	44.4 Kw (0.8/14) 1" inlet & outlet
Gas heating power	29.4 Kw 2 burners ½" connection
Exhaust	20 m³/min (150mm drain Ø) (150 Pa pressure)
Noise	61 Db (A)
Machine dimensions (LxWxH)	874 mm x 801 mm x 1868 mm
Packing dimensions (LxWxH)	890 mm x 840 mm x 1980 mm
Net weight (Reversing)	225 Kg (Gas) 226 Kg (Electric) 232 Kg (Steam)
Gross weight (Reversing)	237 Kg (Gas) 238 Kg (Electric) 243 Kg (Steam)

Detail & Dimensions

